

## Facestock:

A white, one side machine coated, woodfree printing paper with semi-gloss appearance. The facestock is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451).

The products are suitable for a wide range of promotional and industrial label applications where an attractive semi-gloss appearance, in multi-colour work is required.

Caliper: 69 µm  
Basic Weight: 80 g/m<sup>2</sup>

## Adhesive:

S9500 is an acrylic based permanent biodegradable and compostable adhesive.

Initial Tack: 12.5 N/25mm  
Peel Adhesion 90°: 7 N/25mm  
Min. App. Temp: 5°C  
Temp Range: -20°C to 80°C

The adhesive is characterised by a good initial tack and good adhesion on a wide variety of substrates.

S9500 is compliant with the European food regulation 1935/2004/EC for direct food contact with dry, non-fatty foodstuff. S9500 complies with DIN EN 13432 biodegradability and compostability regulation and is OK Compost certified under the tracking number S0259.

## Liner:

BG40 white, a supercalendered glassine paper.

Caliper: 53 µm  
Basic Weight: 60 g/m<sup>2</sup>

## Laminate:

Total Caliper: 136 µm ± 10%

## Shelf Life:

2 years under storage conditions as defined by FINAT (20- 25°C; 40-50%RH).

## Disclaimer:

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.