

Recycled PP White Spec Sheet



Facestock:

A cavitated white, bi-axially oriented polypropylene film with ISCC-certified recycled content and print-receptive topcoat. Contains >90% recycled content from certified chemically recycled Post-Consumer Recyclate (PCR).

Caliper: 58 μm
Basic Weight: 41 g/m^2

Adhesive:

A general-purpose permanent, acrylic based adhesive.

Initial Tack: 10 N/25mm
Peel Adhesion: 6 N/25mm
Min. App. Temp: 5°C
Temp Range: -20°C to 80°C

The adhesive is clear and permanent, featuring excellent UV resistance and weatherability, together with good adhesion performance, even on apolar substrates.

Liner:

BG40, a white, supercalendered glassine paper.

Caliper: 53 μm
Basic Weight: 59 g/m^2

Laminate:

Total Caliper: 128 $\mu\text{m} \pm 10\%$

Shelf Life:

2 years under storage conditions as defined by FINAT (20- 25°C; 40-50%RH).

Disclaimer:

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.